



Marty's FlexKrete Job Tips

"FlexKrete makes it possible now!"

11/5/2013, VOL. V

SPALL REPAIR with FlexKrete

The quick, easy, effective way!

Buster Wilkerson, of Arris Construction, and his crews, can complete 5,000 s.f. of spalls in one day, using only two men. Also, every detail is attended to, i.e., crack repair, taped, straight lines and job cleanliness. "FlexKrete allows us to come back over our work within an hour and finish, so we can complete large areas the same day." If your work is neat and you do it right, tons of work lie ahead for you. If you do not do this, many times, you won't ever be back. Wilkerson's teams have set the standards for Lowe's and other "large box" company repair work. And they don't mind traveling long distances for small jobs, because they know their excellent workmanship will result in more jobs and locations. Due to hard work and competence, large companies have written their specifications around Wilkerson and his work with FlexKrete. So much so, that many even require a training certificate issued from either his company or FlexKrete. Further, Wilkerson is not afraid of competition. He trains them, and has the foresite to know that there is

plenty of work for every contractor—who renders good service and WHO PAYS ATTENTION TO DETAIL! These two concepts alone, normally result in long-term relationships and continued business, usually, with strong referrals and greater opportunities. Although the technique might vary, depending on the spall depth, the basic process is done in parking lots, inside floors, garden areas, etc.

Clean dirt and contamination from area with scarifier or other equipment. Apply very thin coat of FlexPrime with no puddles or ridges. Let FlexPrime tack. Mix FlexKrete and catalyze. Without adding sand, pour onto area and squeegee with flat squeegee, filling only the spall depressions. Allow to cure for approx. one hour, then roll on coat of catalyzed FlexKrete at about 100 s.f. per gallon, immediately broadcasting the desired aggregate into it. In the picture below, gray, colored quartz was used. Sweep or vacuum any loose material, then spray with FlexSealer for easy cleaning and to help eliminate soiling.

Call FlexKrete for all the details—972-964-8707

